



QW

Widescreen *IP68* Waterproof Weighing Indicator



Features:

- Extra-large and wide LCD display (175 x 70mm) 6 digits with 55mm height
- LCD display with COOL WHITE LED backlight
- RS-232 + RTC (Real Time Clock) interface
- Type 304 stainless steel housing
- IP 68: Mist-proof, waterproof and dustproof
- Up to 1/15,000 display resolution
- Unit switch key for Kilogram (kg) and pound (lb), etc.
- Full range tare, Pre-tare, Auto zero tracking, Sampling counting, Gross/Net Indication
- Hold function, Check mode Lo / Hi / OK, Auto average unit weight, and Animal scale function
- Low power indication and auto power off

Options:

- Waterproof pressure relief valve – for longer lifespan by preventing possible pressure build-up
- Wireless -or- RS-485
- Wireless for distance 10M or 100M available (SPP mode supported)
- Convenient foot switch for Zero, or Tare, or Print



J: 334 x 254mm



K: 322 x 242mm



S: 300 x 400mm



D: 420 x 520mm



L: 460 x 600mm



F: 400 x 500mm

420 x 520mm

*More sizes are available



Pressure Relief Valve



Specifications:

Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F)

Power Source: Adapter + DC 6V / 4.5Ah rechargeable battery

Dimensions: 232 x 150 x 80mm (W x H x D)

Display: LCD, 6 Digits, 55 mm in height, **COOL WHITE LED** backlight

Display Resolution: 1/15,000(Most Stable) -or- 1/30,000 -or- 1/60,000



EXCELL PRECISION CO., LTD.

6F, No.127, Lane 235, Pao-Chiao Road, Hsin Tien, Taipei Hsien, 231, Taiwan
Tel: +886-2-89191000 Website: www.excell-scale.com
Fax: +886-2-89191177 E-mail: sales@excell-scale.com



QW

Widescreen *IP68* Waterproof Weighing Indicator